



CIE -50FG/A

2021 2

			(B)	(B)
	-50FG/A	1		

1)

2) 1

3)

4) 7 PID USB

5)

6)

7)

8)

9)

10)

3.1

A		
1		5.6K (380)
2		
3		1150 800 1410
4		440KG
5		25
B		
1		0.54 2
2		22 1020
		16 1940
		12 13690
3		6K /
4		10KG/
C		
		0.54 2

		/ /	
1		304 / 4	1
2		304	1
		320 430	4 +1
3			1
4		-100	4
5		-100	2
1			
2			
3		0.8	
4		1 /	
5		0.54 2	
6		-50	
7		+70	
8		1	

9		70	
10			
11			
12			
13		110	
14			
1		304	
2		0.3	
3			
4		1 ID	
5			
6		A	
D			
		/ /	
1		304	1

2		10 1	1
3			1
4		-100	1
1			
2			
3		0.5	
4		-80	
5		10. /	
6			
7		1	
1		304	
2		A	
E			
		/ /	

1			2
2		23	
		404	
3		D	2
4		A	1
5			8
6		D	2
7			2
8			1
1		+20 -40 60	
2		+20 -40 60	
3			
1			
2			

3			
4			
5			
5			
F			
		/ /	
1		-24	1
2			1
1		2	
2		10 15	
3		5 10-3 . 3/	
1			
1	KF		

H			
		/ /	
1			1
2		5	15KG
3		1.5K	1
4			1
5		-100	2
6			1
1		1 C/	
2		5 25	
1	ID		
I			
		/ /	
1			

2			4
J			
		/ /	
1		IEC60204-1	
2	C		1
3	A C ()		1
4			1
5			
6			
7			1
8	C		1
9			1
		/ /	
1			

2	
3	
1	FDA
2	
3	
4	40
5	
6	
7	
8	
9	
10	
11	FDA 21CF A II
12	20 C
13	

K		
		/ /
1		

1)

2)

3)

4) /

5

5) :

6) 100%





- 1)
- 2)
- 3)
- 4)
- 5)
- 6)
- 7)
- 8)

+50°C
IP 67

